## **MV** Alkimos

CYPRUS FLAG, BUILT OCT 2013, CLASS LR , UMO No: 9603001 SINGLE DECK BULKCARRIER GEARLESS, POST PANAMAX , JIANGSU EASTERN HEAVY INDUSTRY, CHINA MAN-B&W 6S60ME-C

DWAT 95,308 MT on 15.0 MTRS SSW (moulded) Grain Holds 110,577 CBM - 3,905,000 CFT

7 HO/HA (2 panels side rolling type operated by rack and pinion with electro hydraulic motors. For full opening of hatch one panel opening on each side and for half opening both panels one side)

DIMENSION OF HATCHES METERS (LENGTH X BEAM):

15.30 x 14.60 17.85 x 17.00 17.85 x 17.00 Hatch 1: Hatch 2: Hatch 3: 17.85 x 17.00 17.85 x 17.00 17.85 x 17.00 17.85 x 17.00 15.30 x 14.60 Hatch 4: Hatch 5: Hatch 6: Hatch 7:

13,058.5 17.652.3 16,062.6 567,250.7 567,250.7 623,422.7 4 16,062.6 5 16,062.6 17,653.2 495,310.5 14,025.1 3,905,037.1 110,576.9

LOA: 229.13 mtrs - LBP: 222.85 Mtrs - Beam 38 mtrs (moulded) - Depth 20.70 mtrs (moulded)

Cargo Ventilation: Natural.

GRT/NRT 51984 / 31692

Panama canal/UMS net tonnage: 43829

	DRAUGHT	DWAT SALT	TPC	DWAT FRESH
TROP FRESH	15.678m	-	-	98,387
FRESH	15.365m	-	-	95,890
TROPICAL	15.313m	97,862 MT		
SUMMER	15.05m	95,308 MT	81.5	
WINTER	14.687m	92,758 MT		

(All draughts are moulded and calculated for F.W density 1.000mt/m3 and S.W 1.025mt/m3)

Also vessel holds dual dwt certificates for: 69,999mt dwt at 11.865m Mld draught 79,999mt dwt at 13.112m Mld draught

Tank Top Strengths (all in mt/m2): nr.1/34, nr.2/25, nr.3/31, nr.4/25, nr.5/31, nr.6/25, nr.7/33 All Strengths Basis Uniformly Distributed Loads .

Strengthened For Heavy Cargoes.
Can load in alternate holds (always subject to Master's reconfirmation and always in accordance with class/IACS regulations and rules, Holds No.2,4,6 maybe empty).

Australian Hold Ladders Fitted: Yes

Co2 in holds: Yes A60 bulkhead: Yes

 = Alkimos Navigation Company Limited, Nicosia
 = Blue Planet Shipping Ltd, Piraeus
 = West of England P+I Assoc. (Luxembourg) Owners Managers P & I Club

ALL DETAILS/FIGURES "ABOUT"