

# MV Annita

53,688 MT Supramax

GREEK, 2005 MARCH  
 NKK NS Bulk Carrier ESP, BCA, PS DA & FA, MO CHG MPP LSA RCF  
 complying with IMO NOx Emission limits.  
 IMO NUMBER: 9282869  
 Singledeck 'Double Skin' Bulk Carrier, New Century, China,  
 MAN B+W 6S50MC-C 12,870 BHP

DWAT 53,688 MT on 12.49M / 41FT SSW

About 14.0 on about 32 MT IFO Laden .  
 About 14.0 on abt 29 MT IFO basis light ballast .  
 No MDO At Sea.

PC : about 2.0 LT MDO Gear Idle + 1 about LT MDO  
 Per 8 Hrs Gear Working.

CRANES 4 x 40 MT swl. Max. Outreach 11.87m

4 Sets Electro- hydraulic Grabs  
 Grabs Capacity: 18.5m3 - Density 1.1 MT/m3 8m3 - Density 2.5  
 MT/m3

5 HO/HA (MACGREGOR FOLDING Type - ELECTRO-HYDRAULIC)  
 18.86 / 21.32 / 21.32 / 21.32 / 21.32 xx 18.26 m.

GRAIN Holds FT3/m3	BALE FT3
1. 397,288 /11,250	385,891
2. 504,713 /14,292	486,972
3. 476,474 /13,492	459,694
4. 501,903 /14,212	484,268
5. 441,498 /12,502	430,208
2,321,876 /65,748	2,247,033

Flat Floor Area of Tank Tops (wog)				
FWD	ABT	MID	AFT	LENGTH
7.0	19.4	23.0	23.0	27.88
23.0	23.2	23.2	23.2	28.70
23.2	23.2	23.2	23.2	27.06
23.2	23.2	23.2	23.2	28.70
23.2	19.4	12.0	23.2	27.06

LOA 189.99 m - LBP 182 m - Beam 32.26 m (Moulded) -  
 Depth 17.2m (Moulded)

CO2 In Holds: Yes. - Australian Hold Ladders Fitted: Yes

INTERNATIONAL GT/NT: 31198 / 18391  
 Suez GT/NT: 32650 / 29321 Panama canal/UMS net tonnage : 25880

	DRAFTS	DWAT SALT	TPC	TPI	DWAT FRESH
TROP FR	13.032m	-	-	-	55,154
FRESH	12.772	-	-	-	53,688
TROPICAL	12.750m	55,154 MT	56.57	143.68	53,564
SUMMER	12.490m	53,688 MT	56.39	143.22	52,096
WINTER	12.230m	52,172 MT	56.20	142.74	50,709
Light Ship	: approx. 10019 MT				

Strengths (MT/m2): HATCH: 1.75T/m2  
 DECK SIDES: 2.5T/m2  
 T/T: all holds 25T/m2

All Strengths Basis Uniformly Distributed Loads

Strengthened For Heavy Cargoes.  
 Alternate Hold Loading: 2+4 May Be Empty At The Same Time (always  
 subject to Master's reconfirmation and always in accordance with  
 class/iacs regulations and rules for BCA bulk carrier)

Type Of Hold Ventilation: Natural

Constants: 350 T (Excl. FW)

P&I = West of England  
 Managers = Z&G Halcoussis Co. Ltd, Piraeus



For more details please contact the chartering department on:

Email: chartering@vicsteam.co.uk  
 Tel: +30 210 4599 024 / 683

